



LISTING INFORMATION OF
Tuffco - Cast Iron Fittings
SPEC ID: 46952

Tuffco Inc.
4945 Steeles Avenue West
Toronto, ON M9L 1R4
Canada

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

LISTING INFORMATION

Tuffco manufactures iron fittings for use in drainage applications in below or above soil applications. These products are available in various pipe sizes and fitting sizes.

Tuffco cast iron fitting models evaluated by Intertek are outlined below:

T31400 : Bend ¼ 90 deg. Short Turn fittings
T31800 : Bend 1/8 45 deg. Short Turn fittings
T40410 : 4" x 1½" Y
T40620 : 6" x 2" Y
T41000 : Y fittings
T41040 : Y fittings
T41060 : Y fittings
T41080 : Y fittings
T41870: 4x1 1/2Y Tapped
T43330 : 3" x 3" Y
T43420: 4x2 Combination Y with 1/8 Bend bos
T43440 : 4" x 4" Y
T43660: 6x6 Combination Y with 1/8 Bend bos
T46990 : Upright Y with 1/8 bend fittings
T47000 : Upright Y with 1/8 bend fittings
T47020 : Upright Y with 1/8 bend extended fittings
T47040 : Upright Y with 1/8 bend extended fittings
T47050 : Upright Y with 1/8 bend extended fittings
T47140 : Upright Y with 1/8 bend extended fittings
T47150 : Upright Y with 1/8 bend fittings
T47170 : Upright Y with 1/8 bend fittings
T47180 : Upright Y with 1/8 bend fittings
T47220 : Upright Y with 1/8 bend extended fittings
T47290 : Upright Y with 1/8 bend extended fittings
T50190 : Extended TY fittings
T50200 : 10" x 10" Y
T50620 : 6" x 2" Y
T51840 : 3" x 1½" TY Tapped
T51920: 3x3 TY Long with w/MJ 1 1/2-45 Left
T51930:3x3 TY Long with w/MJ 1 1/2-45 Right
T52000 : Extended Double TY 90 deg Tapped reversible fittings
T52020 : Double TY Special MJ Long Pattern fittings
T52040 : TY Long w / MJ 1 ½ 45 deg fittings
T52050 : TY Long w / MJ 1 ½ 45 deg. fittings
T52510 : Double TY Special MJ Long Pattern fittings
T52520 : Double TY Special MJ Long Pattern fittings
T52710 : Double TY Special MJ Long Pattern fittings
T52720 : Double TY Special MJ Long Pattern fittings
T57870 : Double TY Tapped Cross fittings
T60310 : 3" x 1½" Reducer
T60620 : 6" x 2" Reducer **

T60830 : 8" x 3" Reducer **
T61040 : 10" x 4" Reducer **
T61060 : Increasers / Reducers fittings
T61080 : Increasers / Reducers fittings
T61100: 12x6 Increaser/Reducer
T62170: 3" P Traps with 1/2" Primer Tap
T62320: 2" P Traps Deep Seal
T62390: 3" Trap Seal Primer Connection
T62400: 4" Trap Seal Primer Connection
T63100: 10 Plugs- Hubless (MJ)"

Attribute	Value
Criteria	CSA B70 (2006)
Criteria	CSA B70 (2012)
CSI Code	22 13 16 Sanitary Waste and Vent
Listing Section	DWV, DRAIN & SEWER
Spec ID	46952