## **Product Certification Listing**

**CERTIFIED BY INTERTEK** 

**PCL - 1001** 

Issue Date: August 23, 2022 Revision Date: August 23, 2022



Company: American Original Building

Products LLC 1001 Arlington Circle Akron, OH 44306 American Original Building Products Polypropylene Siding products are molded, polypropylene siding conforming to ASTM D7254, as exterior wall covering.

1. LISTING

Listing Ref: Intertek Spec ID: 69054
Category: Polypropylene Siding

**CSI Section:** 07 46 33 Plastic Siding

Certification Scheme: VSI Product Certification Program

Vinyl Siding Institute, Inc.

Standards: ASTM D7254-21 Standard Specification for

Polypropylene (PP) Siding

## 2. PRODUCTS

**Certified Products and Standard Design Pressure Rating** 

Brand	Product	Style	Design Pressure (PSF)
American Original Building Products	American Original Shake and Scallop Siding	Cape Cod <sup>(1)</sup>	83
		Cedar Shake <sup>(1)</sup>	138
		Hand-split Shake(2)	83
		Scallop <sup>(2)</sup>	101

<sup>(1)</sup> Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 2-1/2-inch long, 1/8-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 16 inches o.c. for horizontal siding with every nail penetrating wood framing.

**Identification:** Products covered by this listing are identified with labels that include the following:

American Original Building Products Production lot identification VSI certification mark Product Certification Listing (PCL) No, standards and related ratings Certified By Intertek: ASTM D7254 Std Design Pressure Rating:

## PSF (ASD)



CERTIFICATION PROGR

PCL-1001

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name, one of its marks or the VSI mark for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 1 of 1



<sup>(2)</sup> Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 2-1/2-inch long, 1/8-inch ring shank diameter nail with a 7/16-inch head diameter. Spacing shall be 16 inches o.c. for horizontal siding with every nail penetrating wood framing.