Product Certification Listing

CERTIFIED BY INTERTEK

PCL - 0601

Issue Date: March 22, 2022 Revision Date: September 23, 2024

Company: Associated Materials LLC 3773 State Road Cuyahoga Falls, OH 44223 (330) 922-5384 Associated Materials Vinyl Siding products are extruded, rigid PVC siding conforming to ASTM D3679, as exterior wall covering.

1. LISTING

Listing Ref:	Intertek Spec ID: 66965	Stan
Category:	Vinyl Siding	
CSI Section:	07 46 33 Plastic Siding	
Certification Scheme:	VSI Product Certification Program	
	Vinyl Siding Institute, Inc.	

Standards: ASTM D3679-21 Standard Specification for Rigid Poly (Vinyl Chloride) (PVC) Siding or other as appropriate]

2. PRODUCTS

Certified Products and Standard Design Pressure Rating

Brand	Product	Style	Design Pressure (PSF)
Alside	Alliance T4	Triple 4 Vertical ⁽¹⁾	33
	Board & Batten	Single 7" ⁽²⁾	67
	Charter Oak Crained	Double 4-1/2 Clapboard ⁽³⁾	73
	Charter Oak Grained	Double 4-1/2 Dutch Lap ⁽³⁾	73
	Charter Oak Matte	Double 4-1/2 Clapboard ⁽³⁾	73
	Charler Oak Malle	Double 4-1/2 Dutch Lap ⁽³⁾	73
	Charter Oak Soffit	Triple 3-1/3 ⁽³⁾	33
	Charter Oak XL	Double 4-1/2 Clapboard ⁽³⁾	73
		Double 4-1/2 Dutch Lap ⁽³⁾	73
	Charter Oak XL Matte	Double 4-1/2 Clapboard ⁽³⁾	73
	Conquest	Double 4-1/2 Clapboard ⁽³⁾	69
	Conquest	Double 4-1/2 Dutch Lap ⁽³⁾	69
		Double 4 Clapboard ⁽³⁾	47
Ody	Coventry by Alside	Double 4 Dutch Lap ⁽³⁾	47
		Double 5 Clapboard ⁽³⁾	47
		Double 5 Dutch Lap ⁽³⁾	47
		Double 4 Clapboard ⁽³⁾	60
	Odvessy Dive	Double 4 Dutch Lap ⁽³⁾	60
	Odyssey Plus	Double 5 Clapboard ⁽³⁾	60
		Double 5 Dutch Lap ⁽³⁾	60
	Williamsport Colonial Beaded	6-1/2 Beaded ⁽³⁾	55



CREDITED

PCA-101



Product Certification Listing

CERTIFIED BY INTERTEK

PCL - 0601



Issue Date: March 22, 2022 Revision Date: September 23, 2024

Brand	Product	Style	Design Pressure (PSF)
Gentek	Aurora II	Double 4 Clapboard ⁽³⁾	53
		Double 4-1/2 Dutch Lap ⁽³⁾	53
	Concord	Double 4 Clapboard ⁽³⁾	47
		Double 5 Dutch Lap ⁽³⁾	47
		Double 5 ⁽³⁾	47
		Double 4 Dutch Lap ⁽³⁾	47
	Fair Oaks	Double 4 ⁽³⁾	37
		Double 4 Dutch Lap ⁽³⁾	37
		Double 5 ⁽³⁾	37
		Double 4 Dutch Lap ⁽³⁾	37
	Fairweather Soffit/Vertical	"V" Groove Triple 4" ⁽²⁾	31
	Oxford Soffit/Vertical 10	"V" Groove Double 5" ⁽²⁾	44
	Oxford Soffit/Vertical 12	"V" Groove Double 5" ⁽²⁾	44
	Sequoia Board & Batten	7 Vertical ⁽²⁾	78
	Sequoia Select	Double 4 ⁽³⁾	73
		Double 5 Dutch Lap ⁽³⁾	73
		Double 5 ⁽³⁾	73
Se		Double 4-1/2 Dutch Lap ⁽³⁾	73
	Sequoia Vertical Siding	Soffit/Vertical ⁽⁴⁾	47
	Signature Supreme	Double 4 ⁽³⁾	37
		Double 4 Dutch Lap ⁽³⁾	37
		Double 5 ⁽³⁾	37
		Double 5 Dutch Lap ⁽³⁾	37

1. Standard design pressure rating is the maximum allowable negative wind load when installed vertically with 1-1/2-inch long, 1/8-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 6 inch o.c. for vertical siding and penetrating 1/2 inch OSB or plywood sheathing.

2. Standard design pressure rating is the maximum allowable negative wind load when installed vertically with 1-1/2-inch long, 1/8-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 12 inch o.c. for vertical siding and penetrating 1/2 inch OSB or plywood sheathing.

 Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 1-1/2-inch long, 1/8-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 16 inch o.c. for horizontal siding and penetrating wood framing.

4. Standard design pressure rating is the maximum allowable negative wind load when installed vertically with 1-1/2-inch long, 1/8-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 10 inch o.c. for vertical siding and penetrating 1/2 inch OSB or plywood sheathing.



VSI-PCP-PCL: [June 21, 2021]

1800 Diagonal Road, Suite 545 Alexandria, VA 22314 vinylsiding.org Intertek 545 E. Algonquin Road Arlington Heights, IL 60005

PCA-101

Product Certification Listing

CERTIFIED BY INTERTEK

PCL - 0601

Issue Date: March 22, 2022 Revision Date: September 23, 2024



Identification: Products covered by this listing are identified with labels that include the following:

Associated Materials LLC Production lot identification VSI certification mark Product Certification Listing (PCL) No, standards and related ratings Certified By Intertek: ASTM D3679 Std Design Pressure Rating: ## PSF (ASD)



This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name, one of its marks or the VSI mark for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 3 of 3

VSI-PCP-PCL: [June 21, 2021]

1800 Diagonal Road, Suite 545 Alexandria, VA 22314 vinylsiding.org Intertek 545 E. Algonquin Road Arlington Heights, IL 60005

