

Product Certification Listing

CERTIFIED BY INTERTEK



PCL – 0201

Issue Date: February 25, 2022

Revision Date: February 29, 2024

Company: KP Building Products, Ltd.
34 Blair Park Road
Suite 104, PMB 318
Williston, VT 05495
(802) 848-7010

KP Building Products, Ltd. products are extruded, rigid PVC siding conforming to ASTM D3679, as exterior wall covering

1. LISTING

Listing Ref: Intertek Spec ID: 66319
Category: Vinyl Siding
CSI Section: 07 46 33 Plastic Siding

Standards: **ASTM D3679-21** Standard Specification for Rigid Poly (Vinyl Chloride) (PVC) Siding or other as appropriate]

Certification Scheme: VSI Product Certification Program
Vinyl Siding Institute, Inc.

2. PRODUCTS

Certified Products and Standard Design Pressure Rating

Brand	Product Family	Product Style	Design Pressure (PSF)
KP Vinyl Siding	Ashbury	Double 6 ⁽¹⁾	62
	Dakota	Double 4 ⁽¹⁾	67
		Double 4 Dutchlap ⁽¹⁾	73
		Double 5 ⁽¹⁾	67
		Double 5 Dutchlap ⁽¹⁾	73
		Triple 3 ⁽²⁾	49
	Dakota Plus	Double 4 ⁽²⁾	62
		Double 4 Dutchlap ⁽²⁾	53
		Double 5 ⁽²⁾	62
		Double 5 Dutchlap ⁽²⁾	53
	Double 5 Vertical	Double 5 Solid ⁽⁴⁾	47
	Hudson Bay	Double 4 ⁽¹⁾	67
		Double 4 Dutchlap ⁽¹⁾	73
		Double 5 ⁽¹⁾	67
		Double 5 Dutchlap ⁽¹⁾	73
	Maxim	Double 4 ⁽¹⁾	80
		Double 4 Dutchlap ⁽¹⁾	73
		Double 5 ⁽¹⁾	80
		Double 5 Dutchlap ⁽¹⁾	73
	Maxim	Board & Batten ⁽⁴⁾	60
	Maxim Beaded	6.5 Beaded ⁽²⁾	69
	Maxim XL	Double 4 ⁽¹⁾	80
		Double 4 Dutchlap ⁽¹⁾	73
	Maxim XL Plus	Double 5 ⁽¹⁾	56
		Double 5 Dutchlap ⁽¹⁾	73

Page 1 of 4

VSI-PCP-PCL: [June 21, 2021]

1800 Diagonal Road, Suite 545
Alexandria, VA 22314
vinylsiding.org

Intertek
545 E. Algonquin Road
Arlington Heights, IL 60005



Product Certification Listing

CERTIFIED BY INTERTEK

PCL - 0201

Issue Date: February 25, 2022

Revision Date: February 29, 2024



Certified Products and Standard Design Pressure Rating

Brand	Product Family	Product Style	Design Pressure (PSF)
KP Vinyl Siding	Northern Star	8 ⁽²⁾	69
		6.5 Beaded ⁽²⁾	69
		Double 4 ⁽¹⁾	80
		Double 5 ⁽¹⁾	80
		Triple 3 ⁽²⁾	49
		Double 4 Dutchlap ⁽³⁾	116
		Double 4-1/2 Dutchlap ⁽³⁾	116
		Double 5 Dutchlap ⁽³⁾	116
	Northern Star Rustic	Double 4 ⁽¹⁾	80
	Northern Star Rustic	Double 5 Dutchlap ⁽²⁾	53
		Double 5 Vertical ⁽⁴⁾	47
	Pro-Tuff	Double 4 ⁽¹⁾	67
		Double 4 Dutchlap ⁽¹⁾	73
		Double 5 ⁽¹⁾	67
		Double 5 Dutchlap ⁽²⁾	53
	Pro-Tuff Premium	Double 4 ⁽¹⁾	67
		Double 4-1/2 Dutchlap ⁽¹⁾	73
	Weather Side	Double 4-1/2 Dutchlap ⁽¹⁾	73
	Weather Side Plus	Double 4 ⁽²⁾	62
		Double 4 Dutchlap ⁽²⁾	53
		Double 5 ⁽²⁾	62
		Double 5 Dutchlap ⁽²⁾	53
		Double 4 ⁽²⁾	62
KAYCAN	Verona	Double 4 Dutchlap ⁽²⁾	53
ABTco Vinyl Siding	10"	Vertical ⁽¹⁾	67
	CastleGuard	Double 4 ⁽¹⁾	67
		Double 4 Dutchlap ⁽¹⁾	73
	Cedar Creek	Double 4 ⁽¹⁾	67
		Double 4 Dutchlap ⁽¹⁾	73
		Double 4-1/2 Dutchlap ⁽¹⁾	73
		Double 5 ⁽¹⁾	67
		Double 5 Dutchlap ⁽¹⁾	73
	Colorguard	Double 4 ⁽¹⁾	80
		Double 4 Dutchlap ⁽³⁾	116
		Double 4.5 Dutchlap ⁽³⁾	116
	Fairway	Double 4 ⁽²⁾	67
	Harbor Ridge	Double 4 ⁽²⁾	62
		Double 4 Dutchlap ⁽²⁾	53
		Double 4-1/2 Dutchlap ⁽²⁾	53
		Double 5 ⁽²⁾	62
		Double 5 Dutchlap ⁽²⁾	53
		Triple 3 ⁽²⁾	49
		Double 4 ⁽²⁾	62
	Harbor Ridge Plus	Double 4 Dutchlap ⁽²⁾	53
	Harbor Ridge Rustic	Double 4 ⁽²⁾	62
		Double 5 Dutchlap ⁽²⁾	53

Page 2 of 4

VSI-PCP-PCL: [June 21, 2021]

1800 Diagonal Road, Suite 545
Alexandria, VA 22314
vinylsiding.org

Intertek
545 E. Algonquin Road
Arlington Heights, IL 60005



Product Certification Listing

CERTIFIED BY INTERTEK

PCL - 0201

Issue Date: February 25, 2022

Revision Date: February 29, 2024



Certified Products and Standard Design Pressure Rating

Brand	Product Family	Product Style	Design Pressure (PSF)
ABTco Vinyl Siding	Majestic	Double 4 ⁽²⁾	62
		Double 4 Dutchlap ⁽⁴⁾	53
	Timber Crest	Double 4 ⁽¹⁾	80
		Double 4-1/2 Dutchlap ⁽¹⁾	73
	Timber Crest Plus	Double 4 ⁽⁴⁾	80
		Double 4-1/2 Dutchlap ⁽¹⁾	73
	Timber Crest	Board & Batten ⁽¹⁾	60
		6.5 Beaded ⁽²⁾	69
	Waterford	Double 4 ⁽¹⁾	67
		Double 4 Dutchlap ⁽¹⁾	73
		Double 5 ⁽¹⁾	67
		Double 5 Dutchlap ⁽²⁾	53
		Triple 3 ⁽²⁾	49
	Waterford Plus	Double 4 ⁽²⁾	62
		Double 4 Dutchlap ⁽²⁾	53
		Double 5 ⁽²⁾	62
	Waterford Select	Double 4 Dutchlap ⁽¹⁾	116
	WestPointe	Double 4 ⁽¹⁾	80

1. Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 1-1/2-inch long, 1/8-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 16 inch o.c. for horizontal siding and penetrating wood framing.
2. Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 1-1/2-inch long, 1/8-inch shank diameter nail with a 3/8-inch head diameter. Spacing shall be 16 inch o.c. for horizontal siding and penetrating wood framing.
3. Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 2-1/2-inch long, 1/8-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 16 inch o.c. for horizontal siding and penetrating wood framing.
4. Standard design pressure rating is the maximum allowable negative wind load when installed vertically with 1-1/2-inch long, 1/8-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 12 inch o.c. for vertical siding and penetrating 7/16 inch OSB or plywood sheathing.

Product Certification Listing

CERTIFIED BY INTERTEK

PCL - 0201

Issue Date: February 25, 2022

Revision Date: February 29, 2024



Identification: Products covered by this listing are identified with labels that include the following:

KP Building Products, Ltd.

Production lot identification

VSI certification mark

Product Certification Listing (PCL) No, standards and related ratings

Certified By Intertek:

ASTM D3679

Std Design Pressure Rating:

PSF (ASD)



CERTIFICATION PROGRAM

PCL-0201

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name, one of its marks or the VSI mark for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.