Product Certification Listing

CERTIFIED BY INTERTEK

PCL - 0502

Issue Date: March 22, 2022 Revision Date: March 22, 2022



Company: CertainTeed LLC

20 Moores Road Malvern, PA 19355 CedarBoards™ Insulated Siding products are extruded, foam backed rigid PVC siding conforming to ASTM D7793,

as exterior wall covering.

1. LISTING

Listing Ref: Intertek Spec ID: 66955

Category: Insulated Vinyl Siding
CSI Section: 07 46 33 Plastic Siding

Certification Scheme: VSI Product Certification Program

Vinyl Siding Institute, Inc.

Standards: ASTM D7793-21 Standard Specification for Insulated Vinyl Siding

2. PRODUCTS

Certified Products and Standard Design Pressure Rating				
Brand	Product	Style	Design Pressure (PSF)	Thermal Insulation Value (R-value)
CertainTeed	CedarBoards™ Insulated Siding	Single 7 Clapboard ⁽¹⁾	91	2.02
		Double 6 Clapboard ⁽¹⁾	48	2.16
		Single 12 Vertical Board & Batten ⁽²⁾	80	2.73
	CedarBoards™ XL Insulated Siding	Double 6 XL Clapboard ⁽¹⁾	49	2.16
		Single 7 XL Clapboard ⁽¹⁾	136	2.02

Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 2-inch long, 1/8-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 16 inches o.c. for horizontal siding and penetrating wood framing.

Identification: Products covered by this listing are identified with labels that include the following:

CertainTeed LLC
Production lot identification
VSI certification mark
Product Certification Listing (PCL) No, standards
and related ratings

Certified By Intertek:

ASTM D7793 R=#.## Std Design Pressure Rating: ## PSF (ASD)



CERTIFICATION PROGRAM

PCL-0502

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name, one of its marks or the VSI mark for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 1 of 1



Standard design pressure rating is the maximum allowable negative wind load when installed vertically with 2-inch long, 1/8-inch shank diameter nail with a 7/16-inch head diameter.
 Spacing shall be 12 inches o.c. for vertical siding and penetrating 7/16 inch OSB or plywood sheathing.