

Product Certification Listing

CERTIFIED BY INTERTEK



PCL – 0505

Issue Date: June 24, 2024

Revision Date: June 24, 2024

Company: CertainTeed LLC
20 Moores Road
Malvern, PA 19355

Wolverine Vinyl Siding products are extruded, rigid PVC siding conforming to ASTM D3679, as exterior wall covering

1. LISTING

Listing Ref: Intertek Spec ID: 66955
Category: Vinyl Siding
CSI Section: 07 46 33 Plastic Siding
Certification Scheme: VSI Product Certification Program
Vinyl Siding Institute, Inc.

Standards: **ASTM D3679-21** Standard Specification for Rigid Poly (Vinyl Chloride) (PVC) Siding

ASTM E84-21a Standard Test Method for Surface Burning Characteristics of Building Materials

NFPA 268-22 Standard Test Method for Determining Ignitability of Exterior Wall Assemblies Using a Radiant Heat Energy Source

2. PRODUCTS

Certified Products and Standard Design Pressure Rating			
Brand	Product	Style	Design Pressure (PSF)
Wolverine	Wildcreek	Double 4" Traditional Clapboard ⁽¹⁾	56
		Double 5" Traditional Clapboard ⁽¹⁾	51
		Double 5" Dutchlap ⁽¹⁾	51
		Single 8" Clapboard ⁽¹⁾	64
	Prestige	Double 4" Traditional Clapboard ⁽¹⁾	89
		Double 4-1/2" Traditional ⁽¹⁾	82
		Double 4-1/2" Dutchlap ⁽¹⁾	91
	Groveland	Double 4" Traditional Clapboard ⁽¹⁾	47
		Double 4-1/2" Dutchlap ⁽¹⁾	40
		Double 5" Traditional Clapboard ⁽¹⁾	42
		Double 5" Dutchlap ⁽¹⁾	38
	Heartwood	Single 7" Shingle ⁽¹⁾	87
	Board & Batten	Single 7" Vertical ⁽²⁾	80
	Beaded Porch Panel	Beaded T2 Vertical Siding ⁽²⁾	58
	Vertical Siding	Triple 3-1/3" Vertical Siding ⁽²⁾	42

1. Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 1-1/2-inch long, 1/8-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 16 inch o.c. for all siding and penetrating wood framing.
2. Standard design pressure rating is the maximum allowable negative wind load when installed vertically with 1-1/2-inch long, 1/8-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 12 inch o.c. for all siding and penetrating 7/16-inch OSB or plywood sheathing.

Product Certification Listing

CERTIFIED BY INTERTEK



PCL – 0505

Issue Date: June 24, 2024

Revision Date: June 24, 2024

Additional Properties Evaluated

Property	Test Standard	Rating	Assembly Description
Surface Burning	ASTM E84	Flame Spread ≤ 10 Smoke Developed ≤ 700	N/A
Ignition Resistance	NFPA 268	Meets NFPA 268 acceptance criteria for Radiant Heat Flux of 12 kW/m ²	Vinyl siding attached to an exterior wall sheathed with oriented strand board (OSB), covered with a single layer of No. 15 asphalt felt paper.

Identification: Products covered by this listing are identified with labels that include the following:

CertainTeed LLC

Production lot identification

VSI certification mark

Product Certification Listing (PCL) No, standards and related ratings

Certified By Intertek:

ASTM D3679

Std Design Pressure Rating:

PSF (ASD)

ASTM E84

FS ≤ 10

SD ≤ 700



CERTIFICATION PROGRAM

PCL-0505

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name, one of its marks or the VSI mark for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

VSI-PCP-PCL: [Month 00, 0000]

1800 Diagonal Road, Suite 545
Alexandria, VA 22314
vinylsiding.org

Intertek
545 E. Algonquin Road
Arlington Heights, IL 60005

