

Product Certification Listing

CERTIFIED BY INTERTEK



PCL – 0504

Issue Date: May 4, 2022

Revision Date: August 20, 2024

Company: CertainTeed LLC
20 Moores Road
Malvern, PA 19355

CertainTeed LLC Vinyl Siding products are extruded, rigid PVC siding conforming to ASTM D3679, as exterior wall covering

1. LISTING

Listing Ref: Intertek Spec ID: 66955
Category: Vinyl Siding
CSI Section: 07 46 33 Plastic Siding

Certification Scheme: VSI Product Certification Program
Vinyl Siding Institute, Inc.

Standards: **ASTM D3679-21** Standard Specification for Rigid Poly (Vinyl Chloride) (PVC) Siding

ASTM E84-21a Standard Test Method for Surface Burning Characteristics of Building Materials

NFPA 268-22 Standard Test Method for Determining Ignitability of Exterior Wall Assemblies Using a Radiant Heat Energy Source

2. PRODUCTS

Certified Products and Standard Design Pressure Rating

Brand	Product	Style	Design Pressure (PSF)
CertainTeed	Board & Batten	Single 8" Vertical Siding ⁽¹⁾	71
		Single 7" Vertical Siding ⁽²⁾	80
	Carolina Beaded	Single 6.5" Beaded ⁽³⁾	42
	Encore	Double 4-1/2" DutchLap ⁽³⁾	47
		Double 4" Clapboard ⁽³⁾	78
		Double 5" Clapboard ⁽³⁾	58
	Mainstreet	Double 4" Clapboard ⁽³⁾	76
		Double 4" DutchLap ⁽³⁾	64
		Double 5" Clapboard ⁽³⁾	64
		Double 5" DutchLap ⁽³⁾	60
		Triple 3" Clapboard ⁽³⁾	64
		Single 6.5" Beaded ⁽³⁾	64
		Single 8" Clapboard ⁽³⁾	64

VSI Product Certification Program

CERTIFIED BY: INTERTEK



PCL – 0504

Issue Date: May 4, 2022

Revision Date: August 20, 2024

Certified Products and Standard Design Pressure Rating

Brand	Product	Style	Design Pressure (PSF)
CertainTeed	Monogram	Double 5" Clapboard ⁽³⁾	67
		Double 5" DutchLap ⁽³⁾	73
		Double 4" Clapboard ⁽³⁾	116
	Monogram XL	Double 4" Clapboard ⁽³⁾	91
		Double 5" DutchLap ⁽³⁾	64
	Northwoods	Single 9" Staggered Rough-Split ⁽³⁾	71
		Single 7" Straight Edge Rough-Split ⁽³⁾	76
		Single 7" Straight Edge Perfection ⁽³⁾	87
		Single 7" Sawmill Shingles ⁽³⁾	87
	Restoration Classic	Double 5" Clapboard ⁽³⁾	71
		Double 4-1/2" DutchLap ⁽³⁾	76
		Triple 3" Clapboard ⁽³⁾	78
		Double 4" Clapboard ⁽³⁾	87
		Double 4-1/2" Clapboard ⁽³⁾	104
	Vinyl Carpentry	Perimeter T3.3 Vertical Siding ⁽¹⁾	37
		Universal T4 Vertical Siding ⁽¹⁾	40
		IronMax D5 Vertical Siding ⁽¹⁾	40
		Triple 3.3 Vertical Siding ⁽¹⁾	42
		Beaded T2 Vertical Siding ⁽¹⁾	58
	American Legend	Double 5" Clapboard ⁽³⁾	40
		Double 4" Clapboard ⁽³⁾	52
		Double 4-1/2" DutchLap ⁽³⁾	56

(1) Standard design pressure rating is the maximum allowable negative wind load when installed vertically with 1/8 inch shank dia. 7/16 inch head, 1-1/2 inch long roofing nails. Spacing shall be 12 inches o.c. for vertical siding and penetrating into 7/16-inch OSB or plywood.

(2) Standard design pressure rating is the maximum allowable negative wind load when installed vertically with 1/8 inch shank dia. 3/8 inch head, 1-1/2 inch long roofing nails. Spacing shall be 12 inches o.c. for vertical siding and penetrating into 7/16-inch OSB or plywood.

(3) Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 1/8 inch shank dia. 7/16 inch head, 1-1/2 inch long roofing nails. Spacing shall be 16 inches o.c. for horizontal siding with every nail penetrating wood framing.

VSI Product Certification Program

CERTIFIED BY: INTERTEK



PCL – 0504

Issue Date: May 4, 2022

Revision Date: August 20, 2024

Additional Properties Evaluated

Property	Test Standard	Rating	Assembly Description
Surface Burning	ASTM E84	Flame Spread ≤ 10 Smoke Developed ≤ 700	N/A
Ignition Resistance	NFPA 268	Meets NFPA 268 acceptance criteria for Radiant Heat Flux of 12 kW/m ²	Vinyl Siding attached to an exterior wall sheathed, with oriented strand board (OSB), covered with a single layer of No. 15 asphalt felt paper

Identification: Products covered by this listing are identified with labels that include the following:

CertainTeed LLC

Production lot identification

VSI certification mark

Product Certification Listing (PCL) No, standards and related ratings

Certified By Intertek:

ASTM D3679

Std Design Pressure Rating:

PSF (ASD)

ASTM E84

FS ≤ 10

SD ≤ 700



CERTIFICATION PROGRAM

PCL-0504

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name, one of its marks or the VSI mark for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

VSI-PCP-PCL: [June 21, 2021]

1800 Diagonal Road, Suite 545
Alexandria, VA 22314
vinylsiding.org

Intertek
545 E. Algonquin Road
Arlington Heights, IL 60005

