Product Certification Listing

CERTIFIED BY INTERTEK

PCL - 0302

Issue Date: April 11, 2022 Revision Date: April 11, 2022



Company: Westlake Royal Building Products

1550 Universal Road Columbus, OH 43207 Westlake Royal Building Products insulated vinyl siding products are extruded, rigid PVC foam backed siding conforming to ASTM D7793; used as exterior wall covering.

1. LISTING

Listing Ref:Intertek Spec ID: 66214Category:Insulated Vinyl SidingCSI Section:07 46 33 Plastic Siding

Certification Scheme: VSI Product Certification Program

Certified Products and Standard Design Pressure Rating

Vinyl Siding Institute, Inc.

TMQ45IP

Standards: ASTM D7793-21 Standard Specification for

51

Rigid Poly (Vinyl Chloride) (PVC) Siding

ASTM E119-20 Standard Test Methods for Fire Tests of Building Construction and

Materials

2. PRODUCTS

Brand	Product Family	Product Code	Product Style	Design Pressure (PSF)	Thermal Insulation Value (R-value)
Royal	Haven	HAVD6	Double 6" Traditional ⁽¹⁾	71	2.21
		HAVBB10	Double 10" Board & Batten (2)	44	2.08
		HAVD712	Double 7" Traditional- Wire(1)	71	2.42
Exterior Portfolio	CraneBoard	TMT6IP	Triple 6" Traditional-Molded(1)	58	2.21
		TMD7IP	Double 7" Traditional- Molded ⁽¹⁾	62	2.41
		D10BBIP	Double 10" Board & Batten (2)	44	2.14
		TMQ4IP	Quad 4" Traditional(1)	51	2.57

Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 2-1/2-inch long, 0.12-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 16 inches o.c. for horizontal siding and penetrating SPF wood framing.

Quad 4.5" Dutchlap (1)

2.74

^{2.} Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 1-1/2-inch long, 0.12-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 16 inches o.c. for horizontal siding and penetrating SPF wood framing.

Product Certification Listing

CERTIFIED BY INTERTEK

PCL - 0302

Issue Date: April 11, 2022 Revision Date: April 11, 2022



Additional Properties Evaluated						
Property	Test Standard	Rating	Assembly Description			
Fire Resistance	ASTM E119	One-Hour Fire- Resistance-Rated Assembly	See Intertek Design No. WRBP/PS 60-02			

Identification: Products covered by this listing are identified with labels that include the following:

Westlake Royal Building Products
Production date codes
VSI certification mark
Product Certification Listing (PCL) No, standards
and related ratings

Certified By Intertek:

ASTM D7793
R=#.##
Std Design Pressure Rating:
PSF (ASD)
ASTM E119
1 HR



PCL-0302

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name, one of its marks or the VSI mark for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 2 of 2

