# **Product Certification Listing**

CERTIFIED BY INTERTEK

## PCL - 0303

Issue Date: October 27, 2022 Revision Date: October 27, 2022



Company:	Westlake Royal Building Products 2801 Post Oak Blvd, Suite 600 Houston, TX 77056	Stylecrest	The Foundry, Portsmouth, Norandex, Alside and Stylecrest Vinyl Siding products are rigid PVC siding conforming to ASTM D3679, as exterior wall covering	
1. LISTING				
Listing Ref:	Intertek Spec ID: 66214	Standards:	ASTM D3679-21 Standard Specification for	
Category:	Vinyl Siding		Rigid Poly (Vinyl Chloride) (PVC) Siding	
CSI Section:	07 46 33 Plastic Siding			
Certification Scheme:	VSI Product Certification Program Vinyl Siding Institute, Inc.			

#### 2. PRODUCTS

Brand	Product	Style	Design Pressure (PSF)
	10" Staggered Shake	Staggered (1)	75
	7" Staggered Shake	7" Shake <sup>(1)</sup>	100
	Perfection Shingles	7" Shingle <sup>(2)</sup>	109
Westlake Royal Building Products	Split Shakes	7" Shake <sup>(2)</sup>	109
The Foundry	Rounds Shapes	6" Rounds <sup>(1)</sup>	108
	Transitional Starter	6" Shingle <sup>(1)</sup>	108
	Grayne Shingle	5" Shingle (3)	108
	Grayne Shingle	7.5" Shingle <sup>(3)</sup>	88
Westlake Royal Building Products Portsmouth	Foundry FPX Shingle	Cedar Shingles <sup>(2)</sup>	109
	10" Staggered Shake	Staggered <sup>(1)</sup>	75
	7" Staggered Shake	7" Shake <sup>(1)</sup>	100
	Perfection Shingles	7" Shingle <sup>(2)</sup>	109
Norandex	Cedar Shingle	Cedar Shingles (2)	109
	Split Shakes	7" Shake <sup>(2)</sup>	109
	Rounds Shapes	6" Rounds <sup>(1)</sup>	108
	Transitional Starter	6" Shingle (1)	108

1800 Diagonal Road, Suite 545 Alexandria, VA 22314

vinylsiding.org



Intertek 545 E. Algonquin Road Arlington Heights, IL 60005 Page 1 of 2

## VSI Product Certification Program

CERTIFIED BY: INTERTEK

## PCL - 0303



Issue Date: October 27, 2022 Revision Date: October 27, 2022

Certified Products and Standard Design Pressure Rating					
Brand	Product	Style	Design Pressure (PSF)		
Associated Materials Alside	10" Staggered Shake	Staggered (1)	75		
	Perfection Shingles	7" Shingle <sup>(2)</sup>	109		
	Split Shakes	7" Shake <sup>(2)</sup>	109		
	Rounds Shapes	6" Rounds <sup>(1)</sup>	108		
	Transitional Starter	6" Shingle <sup>(1)</sup>	108		
Stylecrest	Split Shakes	7" Shake <sup>(2)</sup>	109		

(1) Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 1-1/2-inch long, 1/8-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 8 inches o.c. for horizontal siding and penetrating 7/16-inch OSB or plywood sheathing.

<sup>(2)</sup> Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 1-1/2-inch long, 1/8-inch shank diameter nail with a 3/8-inch head diameter. Spacing shall be 10 inches o.c. for horizontal siding and penetrating 7/16-inch OSB or plywood sheathing.

<sup>(3)</sup> Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 1-1/2-inch long, 1/8-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 16 inches o.c. for horizontal siding and penetrating wood framing.

Identification: Products covered by this listing are identified with labels and or packaging that include the following:

Westlake Royal Building Products Product date codes VSI certification mark Product Certification Listing (PCL) No, standards and related ratings

**Certified By Intertek: ASTM D3679** Std Design Pressure Rating: ## PSF (ASD)



PCL-0303

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name, one of its marks or the VSI mark for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

VSI-PCP-PCL: [June 21, 2021]

1800 Diagonal Road, Suite 545 Alexandria, VA 22314 vinylsiding.org





