

Product Certification Listing

CERTIFIED BY INTERTEK



PCL - 0301

Issue Date: April 11, 2022

Revision Date: May 21, 2025

Company: Westlake Royal Building Products
1550 Universal Road
Columbus, OH 43207

Westlake Royal Building Products vinyl siding products are extruded, rigid PVC siding conforming to ASTM D3679; used as exterior wall covering.

1. LISTING

Listing Ref: Intertek Spec ID: 66214
Category: Vinyl Siding
CSI Section: 07 46 33 Plastic Siding

Certification Scheme: VSI Product Certification Program
Vinyl Siding Institute, Inc.

Standards: **ASTM D3679-21** Standard Specification for Rigid Poly (Vinyl Chloride) (PVC) Siding
ASTM E119-20 Standard Test Methods for Fire Tests of Building Construction and Materials

2. PRODUCTS

Certified Products and Standard Design Pressure Rating

Brand	Product Family	Product Code	Product Style	Design Pressure (PSF)
Royal	Woodland	RWD45	Double 4.5" Traditional ⁽¹⁾	73
		RWD45D	Double 4.5" Designer ⁽¹⁾	80
		RBB7	Board and Batten ⁽²⁾	69
	Estate	ESTD4	Double 4" Traditional ⁽³⁾	80
		ESTD45D	Double 4.5" Designer ⁽³⁾	80
		ESTD5D	Double 5" Designer ⁽³⁾	52
		RCCOL6	Single 6" Beaded ⁽³⁾	93
	Residential	RED4	Double 4" Traditional ⁽¹⁾	47
		RED45	Double 4.5" Traditional ⁽¹⁾	64
		RED45D	Double 4.5" Designer ⁽¹⁾	64
		RED5	Double 5" Traditional ⁽¹⁾	47
		RET3D	Triple 3" Traditional ⁽¹⁾	64
	Crest	RCD4	Double 4" Traditional ⁽¹⁾	58
		RCD4D	Double 4" Designer ⁽¹⁾	58
		RCD45D	Double 4.5" Designer ⁽¹⁾	53
		RCD5	Double 5" Traditional ⁽¹⁾	47
		RCD5D2	Double 5" Designer ⁽¹⁾	47
		RCD4V10	Vertical Double 4" ⁽²⁾	40
		RC8	Single 8" Traditional ⁽¹⁾	47
	Soffit as Siding	RSD5VSBF	Vertical Double 5" ⁽¹⁾	29
	Genesis (Crest)	GEND45	Double 4.5" Traditional ⁽¹⁾	53
		GEND45D	Double 4.5" Designer ⁽¹⁾	53
		GENT3	Triple 3" Traditional ⁽¹⁾	53
Exterior Portfolio	Premium Point 360	D4PPTM	Double 4" Traditional ⁽¹⁾	122
		D45PPTM	Double 4.5" Dutchlap ⁽¹⁾	67
		BB7	Board and Batten ⁽²⁾	69

Product Certification Listing

CERTIFIED BY INTERTEK

PCL - 0301

Issue Date: April 11, 2022

Revision Date: May 21, 2025



Brand	Product Family	Product Code	Product Style	Design Pressure (PSF)
Exterior Portfolio	Market Square	D4STD	Double 4" Traditional ⁽¹⁾	60
		D45DLSTD	Double 4.5" Dutchlap ⁽¹⁾	82
		D5STD	Double 5" Traditional ⁽¹⁾	55
	Carolina Sands	S65B	Single 6" Beaded ⁽¹⁾	49
		D4CEDAR	Double 4" Traditional ⁽¹⁾	62
	Parkview	D4DCG	Double 4" Dutchlap ⁽¹⁾	62
		D5CEDAR	Double 5" Traditional ⁽¹⁾	57
		D5DCG	Double 5" Dutchlap ⁽¹⁾	57
		D4EG	Double 4" ⁽¹⁾	78
	Elm Grove	D4DLEG	Double 4" Dutchlap ⁽¹⁾	78
		D5DLEG	Double 5" Dutchlap ⁽¹⁾	78
		T4SS	Vertical Triple 4" ⁽⁵⁾	36
	Soffit as Siding	PPSS	Vertical Triple 3 1/3" ⁽⁵⁾	35
		D5SA	Double 5" ⁽⁵⁾	53

- Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with standard fastening defined as: 1-1/2-inch long, 0.12-inch shank diameter nail with a 7/16-inch head dia. Spacing shall be 16" o.c. for horizontal siding and penetrating into SYP wood framing.
- Standard design pressure rating is the maximum allowable negative wind load when installed vertically with standard fastening defined as: 1-1/2-inch long, 0.12-inch shank diameter nail with a 7/16-inch head dia. Spacing shall be 12" o.c. for vertical siding and penetrating into 1/2-inch OSB or plywood sheathing.
- Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with standard fastening defined as: 1-1/2-inch long, 0.12-inch shank diameter nail with a 3/8-inch head dia. Spacing shall be 16" o.c. for horizontal siding and penetrating into SPF wood framing.
- Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with standard fastening defined as: 1-1/2-inch long, 0.12-inch shank diameter nail with a 7/16-inch head dia. Spacing shall be 16" o.c. for horizontal siding and penetrating into SPF wood framing.
- Standard design pressure rating is the maximum allowable negative wind load when installed vertically with standard fastening defined as: 1-1/2-inch long, 0.12-inch shank diameter nail with a 3/8-inch head dia. Spacing shall be 12" o.c. for vertical siding and penetrating into 1/2-inch OSB or plywood sheathing.

Additional Properties Evaluated

Property	Test Standard	Rating	Assembly Description
Fire-Resistance	ASTM E119	One-Hour Fire-Resistance-Rated Assembly	See Intertek Design No. WRBP/PS 60-01

Identification: Products covered by this listing are identified with labels and or packaging that include the following:

Westlake Royal Building Products

Product date codes

VSI certification mark

Product Certification Listing (PCL) No, standards and related ratings

Certified By Intertek:

ASTM D3679

Std Design Pressure Rating:

PSF (ASD)

ASTM E119

1 HR



CERTIFICATION PROGRAM

PCL-0301

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name, one of its marks or the VSI mark for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 2 of 2

VSI-PCP-PCL: [June 21, 2021]

1800 Diagonal Road, Suite 545
Alexandria, VA 22314
vinylsiding.org

Intertek
545 E. Algonquin Road
Arlington Heights, IL 60005

