

# Product Certification Listing

CERTIFIED BY INTERTEK



## PCL - 0402

Issue Date: March 22, 2022

Revision Date: March 22, 2022

**Company:** Provia LLC  
2150 State Route 39  
Sugarcreek, OH 44681  
provia.com  
(330) 852-4711

Provia Insulated Vinyl Siding products are extruded, foam backed rigid PVC siding conforming to ASTM D7793, as exterior wall covering.

### 1. LISTING

**Listing Ref:** Intertek Spec ID: 66776  
**Category:** Insulated Vinyl Siding  
**CSI Section:** 07 46 33 Plastic Siding

**Standards:** ASTM D7793-21 Standard Specification for Insulated Vinyl Siding

**Certification Scheme:** VSI Product Certification Program  
Vinyl Siding Institute, Inc.

### 2. PRODUCTS

#### Certified Products and Standard Design Pressure Rating

Brand	Product	Style	Design Pressure (PSF)	Thermal Insulation Value (R-value)
Provia	CedarMAX 12'	Double 6 <sup>(1)</sup>	62	2.43
		Single 7 <sup>(1)</sup>	62	2.31
	CedarMAX 16'	Double 6 <sup>(1)</sup>	62	2.43
		Triple 4 Dutchlap <sup>(1)</sup>	62	2.84
	Cedar Peaks	8" Board 'n Batten <sup>(2)</sup>	78	2.21
	CedarMAX	8" Board 'n Batten <sup>(2)</sup>	78	2.21

- Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 2-inch long, 1/8-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 16 inch o.c. for horizontal siding and penetrating wood framing.
- Standard design pressure rating is the maximum allowable negative wind load when installed vertically with 2-1/2-inch long, 1/8-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 12 inch o.c. for vertical siding and penetrating 1/2 inch OSB or plywood sheathing.

**Identification:** Products covered by this listing are identified with labels that include the following:

**Provia LLC**  
**Production lot identification**  
**VSI certification mark**  
**Product Certification Listing (PCL) No, standards and related ratings**

**Certified By Intertek:**  
ASTM D7793  
R=#.##  
Std Design Pressure Rating:  
## PSF (ASD)



CERTIFICATION PROGRAM

**PCL-0402**

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name, one of its marks or the VSI mark for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.