

Product Certification Listing

CERTIFIED BY INTERTEK



PCL – 0801

Issue Date: May 19, 2022

Revision Date: March 21, 2024

Company: Norandex Building Materials Distribution
1 ABC Parkway
Beloit, Wisconsin 53511

Norandex Vinyl Siding products are extruded, rigid PVC siding conforming to ASTM D3679, as exterior wall covering

1. LISTING

Listing Ref: Intertek Spec ID: 67782

Category: Vinyl Siding

CSI Section: 07 46 33 Plastic Siding

Standards: **ASTM D3679-21** Standard Specification for Rigid Poly (Vinyl Chloride) (PVC) Siding

Certification Scheme: VSI Product Certification Program
Vinyl Siding Institute, Inc.

2. PRODUCTS

Certified Products and Standard Design Pressure Rating

Brand	Product	Style	Design Pressure (PSF)
Norandex	Board & Batten	Single 7 Vertical ⁽¹⁾	80
	Cambridge	Full-Beaded 6-½ ⁽²⁾	42
	Cedar Knolls	Double 4 Horizontal ⁽²⁾	56
		Double 5 Horizontal ⁽²⁾	56
		Double 5 DutchLap ⁽²⁾	56
	Great Barrier	Double 4 Horizontal ⁽²⁾	78
		Double 5 Horizontal ⁽²⁾	78
		Double 5 DutchLap ⁽²⁾	78
	Great Barrier XL	Double 4 Horizontal ⁽²⁾	78
		Double 5 Horizontal ⁽²⁾	78
		Double 5 DutchLap ⁽²⁾	78
	Premium D5 Vertical Vinyl Siding	Double 5 Vertical ⁽²⁾	33
	Sterling	Single 8 Horizontal ⁽²⁾	44

Product Certification Listing

CERTIFIED BY INTERTEK

PCL – 0801

Issue Date: May 19, 2022

Revision Date: March 2, 2023



Certified Products and Standard Design Pressure Rating

Brand	Product	Style	Design Pressure (PSF)
Norandex	Summit Manor	Double 4.5 DutchLap ⁽³⁾	40
		Double 4 Horizontal ⁽³⁾	47
		Double 5 Horizontal ⁽³⁾	42
		Double 4 Horizontal ⁽²⁾	71
	Woodsman Select	Double 4 DutchLap ⁽²⁾	71
		Double 5 DutchLap ⁽²⁾	31
		Double 5 Horizontal ⁽²⁾	31
	Beaded Porch Panel	Triple 2" Vertical ⁽¹⁾	58

- (1) Standard design pressure rating is the maximum allowable negative wind load when installed vertically with 1/8-inch shank dia. 7/16-inch head, 1-1/2-inch-long roofing nails. Spacing shall be 12 inches o.c. for vertical siding and penetrating 7/16-inch OSB or plywood.
- (2) Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 1/8-inch shank dia. 3/8-inch head, 1-1/2-inch-long roofing nails. Spacing shall be 16 inches o.c. for horizontal siding with every nail penetrating wood framing.
- (3) Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 1/8-inch shank dia. 7/16-inch head, 1-1/2-inch-long roofing nails. Spacing shall be 16 inches o.c. for horizontal siding with every nail penetrating wood framing.

Identification: Products covered by this listing are identified with labels that include the following:

Norandex Building Materials Distribution

Production lot identification

VSI certification mark

Product Certification Listing (PCL) No, standards and related ratings

Certified By Intertek:

ASTM D3679

Std Design Pressure Rating:

PSF (ASD)



CERTIFICATION PROGRAM

PCL-0801

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name, one of its marks or the VSI mark for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

VSI-PCP-PCL: [June 21, 2021]

1800 Diagonal Road, Suite 545
Alexandria, VA 22314
vinylsiding.org

Intertek
545 E. Algonquin Road
Arlington Heights, IL 60005



PCA-101