Product Certification Listing

CERTIFIED BY INTERTEK

PCL - 0703

Issue Date: May 12, 2022 Revision Date: August 11, 2025



Company: Ply Gem Residential Solutions

2600 Grand Blvd

Kansas City, MO 64108

Georgia Pacific, Mastic, Ply Gem Performance Collection, TrueWall and Variform Polypropylene Siding products are molded, polypropylene siding conforming to ASTM D7254, as exterior wall covering.

1. LISTING

Listing Ref: Intertek Spec ID: 67027

Category: Polypropylene Siding **CSI Section:** 07 46 33 Plastic Siding

Certification Scheme: VSI Product Certification Program

Vinyl Siding Institute, Inc.

Standards: ASTM D7254-21 Standard Specification for

Polypropylene (PP) Siding

ASTM E119-20 Standard Test Methods for Fire Tests of Building Construction and

Materials

2. PRODUCTS

Certified Products and Standard Design Pressure Rating					
Brand	Product	Style	Design Pressure (PSF)		
Variform	Heritage Cedar	Perfection Shingle Triple 5 (1)	105		
	Heritage Cedar Hand-Split Shingle	Double 9 ⁽¹⁾	114		
	Heritage Cedar Perfection Shingle	Double 7 ⁽¹⁾	105		
	Heritage Cedar Round-Cut Siding	6-1/4 ⁽¹⁾	68		
Georgia Pacific	Cedar Spectrum	Shingle Siding Triple 5 (1)	105		
	Cedar Spectrum Hand-Split Siding	Double 9 (1)	114		
	Cedar Spectrum Round Cut Siding	Double 6-1/4 ⁽¹⁾	68		
	Cedar Spectrum Shingle Siding	Double 7 ⁽¹⁾	105		
TrueWall		TrueWall Round Cut Siding (1)	68		
	Series 1000	TrueWall Perfection Triple 5 Siding (1)	105		
		TrueWall D7 Perfection Shingle (1)	105		
		TrueWall Hand-Split Siding (1)	114		
Ply Gem Performance Collection	Cedar Dimensions Round-Cut Siding	Double 6-1/4 ⁽¹⁾	68		
	Cedar Dimensions Hand-Split Siding	Double 9 (1)	114		
	Cedar Dimensions Shingle Siding	Double 7 ⁽¹⁾	105		
	Cedar Shingles	Shingle Triple 5 (1)	105		

Page 1 of 2



Product Certification Listing

CERTIFIED BY INTERTEK

PCL - 0703

Issue Date: May 12, 2022 Revision Date: August 11, 2025



ertified Products and Standard Design Pressure Rating					
Brand	Product	Style	Design Pressure (PSF)		
Mastic		Double 7 ⁽¹⁾	105		
	Cedar Discovery Perfection Shingle	Triple 5 ⁽¹⁾	105		
	Cedar Discovery Half-Round	Double 6-1/4 ⁽¹⁾	68		
	Cedar Discovery Hand-Split Shake	Double 9 (1)	114		

⁽¹⁾ Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 1-1/2-inch long, 1/8-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 8 inches o.c. for horizontal siding and penetrating 7/16-inch OSB or plywood with every other nail penetrating wood framing.

Additional Properties Evaluated

Property	Test Standard	Rating	Assembly Description
Fire-Resistance	ASTM E119	One-Hour Fire-Resistance-Rated Assembly	See Intertek Design No. PGR/PS 60-02

Identification: Products covered by this listing are identified with labels that include the following:

Ply Gem Residential Solutions Production lot identification VSI certification mark Product Certification Listing (PCL) No, standards and related ratings

Certified By Intertek:

ASTM D7254 Std Design Pressure Rating: ## PSF (ASD) ASTM E119 1 HR



PCL-0703

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name, one of its marks or the VSI mark for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 2 of 2

