

# Product Certification Listing

CERTIFIED BY INTERTEK



## PCL - 0202

Issue Date: February 25, 2022

Revision Date: August 29, 2025

**Company:** KP Building Products  
20 Moores Road  
Malvern, PA 19355  
(833) 921-2677

KP Building Products Insulated Vinyl Siding products are extruded, foam backed rigid PVC siding conforming to ASTM D7793, as exterior wall covering.

### 1. LISTING

**Listing Ref:** Intertek Spec ID: 66319  
**Category:** Insulated Vinyl Siding  
**CSI Section:** 07 46 33 Plastic Siding

**Standards:** ASTM D7793-21 Standard Specification for Insulated Vinyl Siding

**Certification Scheme:** VSI Product Certification Program  
Polymeric Exterior Products Association

### 2. PRODUCTS

#### Certified Products and Standard Design Pressure Rating<sup>1</sup>

Brand	Product	Style	Design Pressure (PSF)	Thermal Insulation Value (R-value)
KP Vinyl Siding	Ashbury I/S	Double 6	91	2.15
ABTco Vinyl Siding	Northern Star I/S	Double 4	120	2.09
	Timber Crest I/S	Double 4	120	2.09

1. Standard design pressure rating is the maximum allowable negative wind load when installed with 2-1/2-inch long, 1/8-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 16 inches o.c. for horizontal siding and penetrating wood framing.

**Identification:** Products covered by this listing are identified with labels that include the following:

**KP Building Products, Ltd.**  
**Production lot identification**  
**VSI certification mark**  
**Product Certification Listing (PCL) No, standards and related ratings**

**Certified By Intertek:**  
ASTM D7793  
R=#.##  
Std Design Pressure Rating:  
## PSF (ASD)



CERTIFICATION PROGRAM  
**PCL-0202**

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name, one of its marks or the VSI mark for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.