

Product Certification Listing

CERTIFIED BY INTERTEK



PCL - 0101

Issue Date: February 24, 2022

Revision Date: April 9, 2025

Company: Kaycan Ltd.
402 Boyer Circle
Williston, VT 05495
(802) 848-7010

Kaycan Ltd. Vinyl Siding products are extruded, rigid PVC siding conforming to ASTM D3679, as exterior wall covering.

1. LISTING

Listing Ref: Intertek Spec ID: 66256
Category: Vinyl Siding
CSI Section: 07 46 33 Plastic Siding

Standards: ASTM D3679-21 Standard Specification for Rigid Poly (Vinyl Chloride) (PVC) Siding or other as appropriate]

Certification Scheme: VSI Product Certification Program
Vinyl Siding Institute, Inc.

2. PRODUCTS

Certified Products and Standard Design Pressure Rating			
Brand	Product	Style	Design Pressure (PSF)
Kaycan	Davinci	Double 4 ⁽¹⁾	62
		Double 4 Dutchlap ⁽¹⁾	53
	Davinci Intense	Board & Batten Single 7" Vertical	80
	Hardwood Valley II	Double 5 Dutchlap ⁽¹⁾	53
		Double 4 ⁽¹⁾	62
	Ocean Park	Bevel Double 4-1/2 ⁽²⁾	56
		Cove Double 4-1/2 Dutchlap ⁽²⁾	73
	Ocean Park XL	D4.5 Ocean Park XL ⁽²⁾	80
		D4.5D Ocean Park XL Dutchlap ⁽²⁾	73
	Platinum	Double 4 ⁽²⁾	67
		Double 4 Dutchlap ⁽²⁾	73
		Triple 3 ⁽¹⁾	49
Timberlake	Richmond	Board & Batten ⁽³⁾	60
		Double 6 ⁽²⁾	62
	Vertical	Board & Batten Woodgrain ⁽³⁾	60
	Avanti USA	Double 4 Dutchlap ⁽²⁾	73
	Classic	Triple 3 Dutchlap ⁽¹⁾	49
	Contessa	Double 5 ⁽²⁾	67
	Elegance	Double 5 Dutchlap ⁽²⁾	73
	Marquis Canada	Double 4 ⁽²⁾	67
	Marquis USA	Double 4 ⁽²⁾	67
	Prova USA	Double 4-1/2 Dutchlap ⁽²⁾	73
	T3 Woodgrain	Triple 3 ⁽¹⁾	49

Product Certification Listing

CERTIFIED BY INTERTEK



PCL - 0101

Issue Date: February 24, 2022

Revision Date: April 9, 2025

1. Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 1-1/2-inch long, 0.125-inch shank diameter nail with a 3/8-inch head diameter. Spacing shall be 16" o.c. for horizontal siding and penetrating wood framing.
2. Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 1-1/2-inch long, 1/8-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 16 inch o.c. for horizontal siding and penetrating wood framing.
3. Standard design pressure rating is the maximum allowable negative wind load when installed vertically with 1-1/2-inch long, 1/8-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 12 inch o.c. for vertical siding and penetrating 7/16 inch OSB or plywood sheathing.

Identification: Products covered by this listing are identified with labels that include the following:

Kaycan Ltd.

Production lot identification

VSI certification mark

Product Certification Listing (PCL) No, standards and related ratings

Certified By Intertek:

ASTM D3679

Std Design Pressure Rating:

PSF (ASD)



CERTIFICATION PROGRAM

PCL-0101

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name, one of its marks or the VSI mark for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Page 2 of 2

VSI-PCP-PCL: [June 21, 2021]

1800 Diagonal Road, Suite 545
Alexandria, VA 22314
vinylsiding.org

Intertek
545 E. Algonquin Road
Arlington Heights, IL 60005

