

# Product Certification Listing

CERTIFIED BY INTERTEK

## PCL – 0303

Issue Date: October 27, 2022

Revision Date: October 27, 2022



**Company:** Westlake Royal Building Products  
2801 Post Oak Blvd, Suite 600  
Houston, TX 77056

The Foundry, Portsmouth, Norandex, Alside and Stylecrest Vinyl Siding products are rigid PVC siding conforming to ASTM D3679, as exterior wall covering

### 1. LISTING

**Listing Ref:** Intertek Spec ID: 66214  
**Category:** Vinyl Siding  
**CSI Section:** 07 46 33 Plastic Siding

**Standards:** **ASTM D3679-21** Standard Specification for Rigid Poly (Vinyl Chloride) (PVC) Siding

**Certification Scheme:** VSI Product Certification Program  
Vinyl Siding Institute, Inc.

### 2. PRODUCTS

| Certified Products and Standard Design Pressure Rating |                      |                               |                       |
|--------------------------------------------------------|----------------------|-------------------------------|-----------------------|
| Brand                                                  | Product              | Style                         | Design Pressure (PSF) |
| Westlake Royal Building Products<br>The Foundry        | 10" Staggered Shake  | Staggered <sup>(1)</sup>      | 75                    |
|                                                        | 7" Staggered Shake   | 7" Shake <sup>(1)</sup>       | 100                   |
|                                                        | Perfection Shingles  | 7" Shingle <sup>(2)</sup>     | 109                   |
|                                                        | Split Shakes         | 7" Shake <sup>(2)</sup>       | 109                   |
|                                                        | Rounds Shapes        | 6" Rounds <sup>(1)</sup>      | 108                   |
|                                                        | Transitional Starter | 6" Shingle <sup>(1)</sup>     | 108                   |
|                                                        | Grayne Shingle       | 5" Shingle <sup>(3)</sup>     | 108                   |
|                                                        | Grayne Shingle       | 7.5" Shingle <sup>(3)</sup>   | 88                    |
| Westlake Royal Building Products<br>Portsmouth         | Foundry FPX Shingle  | Cedar Shingles <sup>(2)</sup> | 109                   |
| Norandex                                               | 10" Staggered Shake  | Staggered <sup>(1)</sup>      | 75                    |
|                                                        | 7" Staggered Shake   | 7" Shake <sup>(1)</sup>       | 100                   |
|                                                        | Perfection Shingles  | 7" Shingle <sup>(2)</sup>     | 109                   |
|                                                        | Cedar Shingle        | Cedar Shingles <sup>(2)</sup> | 109                   |
|                                                        | Split Shakes         | 7" Shake <sup>(2)</sup>       | 109                   |
|                                                        | Rounds Shapes        | 6" Rounds <sup>(1)</sup>      | 108                   |
|                                                        | Transitional Starter | 6" Shingle <sup>(1)</sup>     | 108                   |

Page 1 of 2

VSI-PCP-PCL: [June 21, 2021]

1800 Diagonal Road, Suite 545  
Alexandria, VA 22314  
vinylsiding.org

Intertek  
545 E. Algonquin Road  
Arlington Heights, IL 60005



# VSI Product Certification Program

CERTIFIED BY: INTERTEK



## PCL – 0303

Issue Date: October 27, 2022

Revision Date: October 27, 2022

### Certified Products and Standard Design Pressure Rating

| Brand                          | Product              | Style                     | Design Pressure (PSF) |
|--------------------------------|----------------------|---------------------------|-----------------------|
| Associated Materials<br>Alside | 10" Staggered Shake  | Staggered <sup>(1)</sup>  | 75                    |
|                                | Perfection Shingles  | 7" Shingle <sup>(2)</sup> | 109                   |
|                                | Split Shakes         | 7" Shake <sup>(2)</sup>   | 109                   |
|                                | Rounds Shapes        | 6" Rounds <sup>(1)</sup>  | 108                   |
|                                | Transitional Starter | 6" Shingle <sup>(1)</sup> | 108                   |
| Stylecrest                     | Split Shakes         | 7" Shake <sup>(2)</sup>   | 109                   |

- <sup>(1)</sup> Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 1-1/2-inch long, 1/8-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 8 inches o.c. for horizontal siding and penetrating 7/16-inch OSB or plywood sheathing.
- <sup>(2)</sup> Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 1-1/2-inch long, 1/8-inch shank diameter nail with a 3/8-inch head diameter. Spacing shall be 10 inches o.c. for horizontal siding and penetrating 7/16-inch OSB or plywood sheathing.
- <sup>(3)</sup> Standard design pressure rating is the maximum allowable negative wind load when installed horizontally with 1-1/2-inch long, 1/8-inch shank diameter nail with a 7/16-inch head diameter. Spacing shall be 16 inches o.c. for horizontal siding and penetrating wood framing.

**Identification:** Products covered by this listing are identified with labels and or packaging that include the following:

**Westlake Royal Building Products**

**Product date codes**

**VSI certification mark**

**Product Certification Listing (PCL) No, standards and related ratings**

**Certified By Intertek:**

ASTM D3679

Std Design Pressure Rating:

## PSF (ASD)



CERTIFICATION PROGRAM

**PCL- 0303**

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name, one of its marks or the VSI mark for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**VSI-PCP-PCL:** [June 21, 2021]

1800 Diagonal Road, Suite 545  
Alexandria, VA 22314  
vinylsiding.org

Intertek  
545 E. Algonquin Road  
Arlington Heights, IL 60005

